



LED 5W G24Q BASE 13W PL REPLACEMENT

Commercial



Hospitality



Retail



- Hybrid Installation, Direct or Bypass
- Available in 3500K, 4000K
- 4-Pin G24Q Base
- UL Approved for Damp Locations
- UL Approved for Use in Enclosed Fixtures
- 5 Year Warranty

| SPECIFICATIONS | 40202 5W/LED/PLC/G24Q/35K | 40203 5W/LED/PLC/G24Q/40K |
|--------------------------|------------------------------|------------------------------|
| Type | LED PL REPLACEMENT | LED PL REPLACEMENT |
| Mount | Horizontal / Vertical | Horizontal / Vertical |
| Base | 4-PIN G24Q | 4-PIN G24Q |
| Wattage | 5W | 5W |
| CFL Equivalence | 9W | 9W |
| Voltage - Frequency | 120V-277V | 120V-277V |
| Color Temperature (ANSI) | 3500K | 4000K |
| Lumens | 520 | 520 |
| Efficacy (LPW) | 104 | 104 |
| CRI | 80 | 80 |
| Beam Angle | 260° | 260° |
| Dimmable | NO | NO |
| Rated Lifetime (hrs.) | 50,000 | 50,000 |
| Dia. x MOL | 1.46" x 4.13" | 1.46" x 4.13" |
| Warranty | 5 Years | 5 Years |

Enclosed Fixtures

Horizontal Mounted

Shatterproof

Damp Location

G24Q Base

Vertical Mounted

50,000 HRS

Bypass

